

[illegible]

Architectural cross-section of a building. The roof is gabled with a 7° pitch. The roof structure consists of sandwich panels (50 mm) and metal ribs. The roof height at the ridge is +8,000. The ground level is marked as -2,400 (ур.з.). The building has internal partitions and a central staircase. The floor is made of concrete walls. The roof is supported by a system of ribs and panels. The building has a total width of 47,000. The roof height at the ridge is +8,000. The ground level is marked as -2,400 (ур.з.). The building has internal partitions and a central staircase. The floor is made of concrete walls. The roof is supported by a system of ribs and panels. The building has a total width of 47,000.

The drawing shows a cross-section of a road with a drainage ditch. The ditch has a width of 47000mm and a slope of 8.53%. The elevation of the ditch bottom is -5.070. The road surface is at an elevation of -2.400. The drawing includes stationing markers (И, Ж, Е, Д, Г, В, Б, А) and various dimensions (7000, 5000, 47000, 4500, 2.291, 2.350, 1.600). The ditch is shown with a hatched pattern.

						7/02-21-AP8		
						"Площадка по выращиванию молодняка крупного рогатого скота молочной породы на 10 000 голов" в с. Казинка Шаповковского района, Ставровольского края"		
Изм. Коуч	Лист	N док	Подпись	Дата		Смаг	Лист	Листов
4.исполнит.	Рукинова			01.22	Телятник для разных возрастных групп (позиции 14 – 29 по ГП)	Р	5	
Н. контр	Рукинова			01.22	Разрез 1-1, 2-2, 5-5	ООО "ГЕОпроект"		
ГИП	Кукалов			01.22				